



UIO106

Universal Input/Output Module

The cost and performance optimized design of complex automation solutions involves a large number of different sensor and actuator types. The standard 10 V and 4 mA to 20 mA interfaces are often not sufficient to achieve demanding objectives.

With the UIO106, a single module type covers all common analog and digital signals for inputs and outputs that can be configured individually for each channel. The extensive versatility of the module is rounded off by a wide range of additional functions such as counters, encoders or pulse width modulation. This simplifies the entire process from the quotation phase through planning, programming and commissioning, right up to stockkeeping and servicing. Besides the 6 freely configurable primary channels, up to 6 additional I/O channels with restricted signal types are available.

Features

- 6-channel analog/digital input/output module
- Up to 6 additional channels depending on the required signal type
- Channel-by-channel configurable signal type and direction
- DI / counter / encoder
- DO / PWM
- AI current/voltage, Pt100, Pt1000, TC
- AO current/voltage
- Synchronous clocks / latch / sync out
- Oversampling
- Direct module-to-module communication

Part type designation	Part number
UIO106	00028977-00
UIO106 EC	00038140-00

Common properties	
Basic function	6x (+ 6x) universal digital/analog input/output
System	Bachmann system M100
Analog inputs - voltage	
Number of analog inputs	0 to 6 configurable
Signal standard	$\pm 10 \text{ V}$, $\pm 1 \text{ V}$, $\pm 100 \text{ mV}$, $\pm 10 \text{ mV}$
Measurement range	$\pm 10.5 \text{ V}$; $\pm 1.05 \text{ V}$; $\pm 105 \text{ mV}$; $\pm 10.5 \text{ mV}$ (105 %)
Resolution (ADC)	16 bit
Accuracy at $T_a = +25^\circ\text{C}$	Measurement range $\pm 10 \text{ V}$: 0.05 % FS Measurement range $\pm 1 \text{ V}$: 0.05 % FS Measurement range $\pm 100 \text{ mV}$: 0.05 % FS Measurement range $\pm 10 \text{ mV}$: 0.2 % FS
Connections per input	2 (+/- differential)
Common mode voltage, max.	Measurement range $\pm 10 \text{ V}$: $\pm 1 \text{ V}$ Measurement range $\pm 1 \text{ V}$: $\pm 1 \text{ V}$ Measurement range $\pm 100 \text{ mV}$: -1 V to +4 V Measurement range $\pm 10 \text{ mV}$: $\pm 3 \text{ V}$
Common mode rejection	$\pm 10 \text{ V} \pm 0.04 \text{ % FS/V}$ $\pm 1 \text{ V} \pm 0.08 \text{ % FS/V}$ $\pm 100 \text{ mV} \pm 0.2 \text{ % FS/V}$ $\pm 10 \text{ mV} \pm 0.25 \text{ % FS/V}$
Cross-talk rejection	< 0.01 % FS/V
Internal scan rate, max.	20 kHz
Digital low pass filter cut-off frequency	3500 Hz to 0.875 Hz configurable
Digital low pass filter slope	> 80 dB/decade
Input impedance	> 100 k Ω
Signal cable length, shielded, max.	1000 m
Signal cable length, unshielded, max.	3 m
Interpolation	Optionally configurable (linearly interpolated intermediate values, delayed output)
Oversampling	Yes
Process data	Analog value Analog value with intermediate values Diagnostics channel quality information
Time stamps	No
Analog inputs - current	
Number of analog inputs	0 to 6 configurable
Signal standard	4 mA to 20 mA, $\pm 20 \text{ mA}$
Measurement range	-13 mA to 21 mA, $\pm 21 \text{ mA}$
Resolution (ADC)	16 bit
Accuracy at $T_a = +25^\circ\text{C}$	Measurement range 4 mA to 20 mA: 0.2 % FS Measurement range $\pm 20 \text{ mA}$: 0.1 % FS
Connections per input	2
Common mode voltage, max.	$\pm 6 \text{ V}$
Common mode rejection	$\pm 20 \text{ mA} \pm 0.08 \text{ % FS/V}$ 4 mA to 20 mA $\pm 0.16 \text{ % FS/V}$
Cross-talk rejection	> 60 dB
Internal scan rate, max.	20 kHz
Digital low pass filter cut-off frequency	875 Hz to 0.875 Hz configurable

Analog inputs – current

Digital low pass filter slope	> 80 dB/decade
Input impedance	Measurement range 4 mA to 20 mA: typ. 178 Ω, max. 215 Ω Measurement range ±20 mA: typ. 144 Ω, max. 175 Ω
Signal cable length, shielded, max.	1000 m
Signal cable length, unshielded, max.	3 m
Interpolation	Optionally configurable (linearly interpolated intermediate values, delayed output)
Oversampling	Yes
Process data	Analog value Analog value with intermediate values Diagnostics channel quality information
Time stamps	No

Analog inputs – resistance thermometer (RTD)

Number of analog inputs	0 to 6 configurable
Signal standard	Pt100, Pt1000
Measurement range	-100 °C to +800 °C
Resolution (ADC)	16 bit
Accuracy at T _a = +25 °C	Measurement range Pt100: ±0.15 % FS Measurement range Pt1000: ±0.15 % FS
Connections per input	2-wire measurement (combined for current loop and resistance measurement) 3-wire measurement (current loop has a separate leg) 4-wire measurement (current loop and resistance measurement separated)
Common mode voltage, max.	±3 V
Cross-talk rejection	> 60 dB
Internal scan rate, max.	20 kHz
Digital low pass filter cut-off frequency	875 Hz to 0.875 Hz configurable
Digital low pass filter slope	> 80 dB/decade
Input impedance	> 10 MΩ
Signal cable length, shielded, max.	1000 m
Signal cable length, unshielded, max.	3 m
Interpolation	Optionally configurable (linearly interpolated intermediate values, delayed output)
Oversampling	Yes
Process data	Analog value Analog value with intermediate values Diagnostics channel quality information
Time stamps	No

Analog inputs – thermocouple

Number of analog inputs	0 to 6 configurable
Signal standard	Thermocouples type J, K, T, N, E, R, S, B
Measurement range	Measurement range J: -100 °C to +1200 °C Measurement range K: -50 °C to +1370 °C Measurement range T: -30 °C to +400 °C Measurement range N: -50 °C to +1300 °C Measurement range E: -100 °C to +1000 °C Measurement range R: -30 °C to +1768 °C Measurement range S: -50 °C to +1768 °C Measurement range B: +600 °C to +1820 °C
Resolution (ADC)	16 bit

Analog inputs – thermocouple

Accuracy at $T_a = +25^\circ\text{C}$	Measurement range J: $\pm 0.15\% \text{ FS}$ Measurement range K: $\pm 0.15\% \text{ FS}$ Measurement range T: $\pm 0.3\% \text{ FS}$ Measurement range N: $\pm 0.15\% \text{ FS}$ Measurement range E: $\pm 0.15\% \text{ FS}$ Measurement range R: $\pm 0.25\% \text{ FS}$ Measurement range S: $\pm 0.25\% \text{ FS}$ Measurement range B: $\pm 0.25\% \text{ FS}$
Connections per input	2 (differential)
Cold junction compensation	Internal measuring point: $\pm 5^\circ\text{C}$ Via set value (e.g. from external sensor)
Common mode voltage, max.	$\pm 3\text{ V}$
Common mode rejection	Measurement range J: $\pm 0.40\% \text{ FS/V}$ Measurement range K: $\pm 0.45\% \text{ FS/V}$ Measurement range T: $\pm 1.40\% \text{ FS/V}$ Measurement range N: $\pm 0.65\% \text{ FS/V}$ Measurement range E: $\pm 0.40\% \text{ FS/V}$ Measurement range R: $\pm 0.65\% \text{ FS/V}$ Measurement range S: $\pm 0.65\% \text{ FS/V}$ Measurement range B: $\pm 0.70\% \text{ FS/V}$
Cross-talk rejection	> 60 dB
Internal scan rate, max.	20 kHz
Digital low pass filter cut-off frequency	0.875 Hz to 875 Hz configurable
Digital low pass filter slope	> 80 dB/decade
Input impedance	> 100 k Ω
Signal cable length, shielded, max.	1000 m
Signal cable length, unshielded, max.	3 m
Interpolation	Optionally configurable (linearly interpolated intermediate values, delayed output)
Oversampling	Yes
Process data	Analog value Analog value with intermediate values Diagnostics channel quality information
Time stamps	No

Analog outputs – voltage

Number of analog outputs	0 to 6 configurable
Signal standard	$\pm 10\text{ V}$ 0 V to 10 V
Output range	$\pm 10.5\text{ V}$ 0 V to $+10.5\text{ V}$
Output current per channel, nominal, continuous	$\pm 10\text{ mA}$ in $\pm 10\text{ V}$ mode 20 mA in 0 V to 10 V mode
Resolution (DAC)	14 bit
Accuracy at $T_a = +25^\circ\text{C}$	Output range $\pm 10\text{ V}$: 0.05 % FS Output range 0 V to 10 V: 0.1% FS
Connections per output	2 (+/- differential, isolated)
Common mode voltage, max.	$\pm 1\text{ V}$
Common mode rejection	$\pm 0.02\% \text{ FS/V}$
Cross-talk rejection	> 60 dB

Analog outputs – voltage	
Internal scan rate, max.	20 kHz
Load impedance, min.	Output range ± 10 V: 1 k Ω Output range 0 V to 10 V: 500 Ω (20 mA max.)
Signal cable length, shielded, max.	1000 m
Signal cable length, unshielded, max.	3 m
Process data	Analog value Analog value with intermediate values Diagnostics channel quality information
Analog outputs – current	
Number of analog outputs	0 to 6 configurable
Signal standard	4 mA to 20 mA, 0 mA to 20 mA, 0 mA to 2 mA, 0 μ A to 200 μ A
Output range	4 mA to 21 mA, 0 mA to 21 mA, 0 mA to 2.1 mA, 0 μ A to 210 μ A
Resolution (DAC)	14 bit
Accuracy at $T_a = +25$ °C	Output range 4 mA to 20 mA: ± 0.2 % FS Output range 0 mA to 20 mA: ± 0.2 % FS Output range 0 mA to 2 mA: ± 0.2 % FS Output range 0 μ A to 200 μ A: ± 0.6 % FS
Connections per output	2 (+/- current loop)
Common mode rejection	> 60 dB
Cross-talk rejection	> 60 dB
Internal scan rate, max.	20 kHz
Load impedance, max.	600 Ω
Signal cable length, shielded, max.	1000 m
Signal cable length, unshielded, max.	3 m
Process data	Analog value Analog value with intermediate values Diagnostics channel quality information
Digital Inputs – 24 V	
Number of digital inputs	0 to 6 configurable
Signal standard	IEC 61131-2 configurable type 1/2/3, sinking input / sourcing input
Voltage category, nominal	24 V DC
Signals per supply group	0 to 6 configurable (1 group)
Connections per input	1 (signal)
Signal supply voltage range	18 V DC to 32 V DC
Operating voltage range (high/on)	> +11 V
Off-state voltage (low/off)	< +5 V
Oversupply protection	-8 V DC to 32 V DC
Input current, on-state, nominal	Type 1: 2.8 mA Type 2: 7 mA Type 3: 2.8 mA, source: -3 mA
Input current, off-state, max.	Type 1: min. 1.5 mA / max. 6 mA Type 2: min. 5 mA / max. 10 mA Type 3: min. 1.5 mA / max. 6 mA
Signal on delay, max.	< 1 μ s + digital spike filter setting time
Signal off delay, max.	< 1 μ s + digital spike filter setting time

Digital Inputs - 24 V

Digital spike filter	Off (0); 16 µs (1); 32 µs (2); 64 µs (3); 128 µs (4); 256 µs (5); 512 µs (6); 1 ms (7); 2 ms (8); 4 ms (9); 8 ms (10); 16 ms (11); 33 ms (12); 66 ms (13); 131 ms (14); 262 ms (15)
Internal scan rate, max.	No internal cycle
Maximum input frequency	150 kHz
Signal inversion	6x
Impulse extension	No
Oversampling	Up to 128 values per cycle (6x)
Process data	Digital state (6x) Digital state with intermediate values (6x) Time stamp rising edge (6x) Time stamp falling edge (6x) Edge detection last bus cycle (6x) Diagnostics channel quality information (6x)
Time stamps	Rising/falling edge (6x)
Signal state indication	Yes (green numeric LED per channel)
Signal cable length, shielded, max.	1000 m
Signal cable length, unshielded, max.	1000 m
Signal supply monitoring	Yes

Digital inputs - TTL

Number of digital inputs	0 to 6 configurable
Signal standard	TTL
Voltage category, nominal	5 V DC
Connections per input	1 (signal)
Signal supply voltage range	18 V DC to 32 V DC
Operating voltage range (high/on)	1.6 V DC to 30 V DC
Off-state voltage (low/off)	-8 V DC to 0.8 V DC
Oversupply protection	-8 V DC to 32 V
Input impedance	> 10 kΩ @ 5 V
Input current, on-state, nominal	3 mA
Input current, off-state, max.	6 mA
Maximum input frequency	150 kHz
Digital spike filter	Off (0); 16 µs (1); 32 µs (2); 64 µs (3); 128 µs (4); 256 µs (5); 512 µs (6); 1 ms (7); 2 ms (8); 4 ms (9); 8 ms (10); 16 ms (11); 33 ms (12); 66 ms (13); 131 ms (14); 262 ms (15)
Time stamps	Rising/falling edge (6x)
Signal state indication	Yes (green numeric LED per channel)
Signal supply monitoring	Yes

Digital inputs - 5 V/24 V pull up

Number of digital inputs	0 to 6 configurable
Signal standard	5 V sourcing input
Voltage category, nominal	5 V DC
Connections per input	1 (signal)
Signal supply voltage range	18 V DC to 32 V DC
Operating voltage range (high/on)	1.6 V DC to 30 V DC

Digital inputs - 5 V/24 V pull up	
Off-state voltage (low/off)	-8 V DC to 0.8 V DC
Overvoltage protection	-8 V DC to 0.8 V DC
Input impedance	> 0.83 kΩ
Input current, on-state, nominal	3 mA
Maximum input frequency	150 kHz
Digital spike filter	Off (0); 16 µs (1); 32 µs (2); 64 µs (3); 128 µs (4); 256 µs (5); 512 µs (6); 1 ms (7); 2 ms (8); 4 ms (9); 8 ms (10); 16 ms (11); 33 ms (12); 66 ms (13); 131 ms (14); 262 ms (15)
Time stamps	Rising/falling edge (6x)
Signal state indication	Yes (green numeric LED per channel)
Signal supply monitoring	Yes
Digital outputs - 24 V	
Number of digital outputs	0 to 6 configurable
Signal standard	IEC 61131-2 type 0.1 A Source (HighSide, sourcing output) / sink (LowSide, sinking output) / push-pull
Voltage category, nominal	24 V DC
Output type	Semiconductor output not isolated
Signals per supply group	0 to 6 (1 group)
Signal supply voltage range	18 V DC to 32 V DC
Overvoltage protection	-8 V DC to 32 V
Connections per output	1 (signal)
Output current per channel, nominal, continuous	0.1 A
Output current per channel, max.	0.1 A
Output current per channel, short-term overload	0.505 A @ $T_a \leq 70^\circ\text{C}$
Output current per group, max.	6x 800 mA short-circuit electricity results in total max. 4.8 A
Output current per channel, min.	0 mA
Output current per channel, off-state, max.	120 µA maximum leakage current
Paralleling outputs	Yes (up to 6 outputs)
Coupled outputs	Yes (up to 6 outputs)
Voltage drop, on-state, max.	450 mV @ 0.1 A
Output impedance, on-state, max.	4.5 Ω
Signal on delay, max.	< 1 µs
Signal off delay, max.	< 1 µs
Internal scan rate, max.	No internal cycle
Maximum output frequency	125 kHz
Signal inversion	6x
Pulsetrains	Up to 128 values per cycle (6x)
Time triggered output	Absolute time set value for output (6x)
Fail safe breaking via common supply	No
Signal state indication	Yes (green numeric LED per channel)
Process data	Digital state (6x) Digital state with intermediate values (6x) Output event (6x) Read-back digital state (6x) Diagnostics channel quality information (6x)

Pulse width modulation (PWM)	
Number of PWMs	0 to 6 configurable
Selectable output interfaces	IEC 61131-2 type 0.1 A Source (HighSide, sourcing output) / sink (LowSide, sinking output) / push-pull
Operation modes	Flexible, parameters can optionally be set as process values: Cycle time Mark-to-space ratio Start pulse duration Pulse rate setting
Cycle time	8 µs to 4.295 s (32 bit)
Duty cycle	0 % to 100 % of cycle time (16 bit)
Settings resolution	1 ns
Impulse duration, min.	8 µs
Energy saving mode	Constant start pulse configurable duration Holdup-pulsing with configurable period and mark-to-space ratio
Coupled PWM	Via coupled digital channel
Time measurement	
Number of time measurements	0 to 2 configurable
Selectable input interfaces	Digital Inputs – 24 V Digital inputs - TTL Digital Inputs - 5 V / 24 V Pull up
Edge evaluation	2x
Cycle time measurement	2x
Pulse duration measurement	2x
Maximum input frequency	150 kHz
Time resolution	10 ns
Process data	Cycle time (2x) Period time stamp (2x) Pulse duration (2x) Pulse duration time stamp (2x) Diagnostics channel quality information (2x)
Counter	
Number of counters	0 to 2 configurable
Selectable input interfaces	Digital Inputs – 24 V Digital inputs - TTL Digital Inputs - 5 V / 24 V Pull up
Edge evaluation	2x (rising/falling/both)
Edge counter including frequency reduction	No
Counter latch	Via DI (2x)
Conditional counting (gate)	Via DI (2x) Via software (2x)
Selectable counting direction	Via DI (2x) Via software (2x)
Frequency measurement	Yes (last period)
Set/reset counter	Via DI (2x) Via software (2x)
Automatic compare function	Upper/lower comparison value (2x)
Maximum input frequency	150 kHz

Counter

Process data	Counter value (2x) Counter value time stamp (2x) Homing state (2x) Homing time stamp (2x) Homing counter value change (2x) Counter value for trigger (2x) Counter value at trigger time stamp (2x) High comparison value status (2x) High comparison value time stamp (2x) Low comparison value status (2x) Low comparison value time stamp (2x) Diagnostics channel quality information (2x)
--------------	--

Incremental position encoder

Number of encoders	0 to 2 configurable
Selectable input interfaces	Digital inputs - HTL (sink/source) Digital inputs - TTL (sink/source)
2-phase quadrature encoding (A/B track)	Single, double, quad edge evaluation (2x)
Edge counting modes	Single, double, quad edge evaluation, pulse/direction (2x)
Counter latch	No
Cycle time measurement	No
Pulse duration measurement	No
Frequency measurement	No
Set/reset encoder	Via software (2x)
Automatic compare function	Upper/lower comparison value (2x)
Automatic increment of compare value	No
Maximum count frequency	500 kHz (quad edge evaluation)
Process data	Position value (2x) Position value time stamp (2x) High comparison value status (2x) High comparison value time stamp (2x) Low comparison value status (2x) Low comparison value time stamp (2x) Diagnostics channel quality information (2x)

Sensor/actuator supply 24 V DC

Number of supply points 24 V DC	0 to 6 configurable (DO function of the channel)
Output current per channel, nominal, continuous	0.1 A

Sensor/actuator supply 0 V to 10 V DC

Number of supply points 0-10 V DC	0 to 6 configurable (AOV function of the channel)
Output current per channel, nominal, continuous	20 mA
Output current per channel, short-term overload	20 mA
Output current per group, nominal, continuous	20 mA
Short-circuit protected, supply	Yes, continuously
Overvoltage protection	±27 V to GND

Sensor/actuator supply 5 V DC

Number of supply points 5 V DC	0 to 6 (AOV function of the channel)
Output current per channel, nominal, continuous	20 mA
Output current per channel, short-term overload	20 mA
Output current per group, nominal, continuous	20 mA

Sensor/actuator supply 5 V DC	
Short-circuit protected, supply	20 mA
Oversupply protection	±27 V to GND
Module-to-module communication	
Signal propagation to neighbour	DI (6x)
Signal receiver from neighbor modules	DO (4x)
Signal propagation delay	300 ns (transmitter + receiver)
Module bus interface	
System	M100
Slot type	IO (1/E, 2, 3, 4, ...31)
Module data rate	Typ.: 0 Mbit/s to 33.6 Mbit/s depending on the configuration
Bus cycle time, min.	4.5 µs ¹⁾
1) Depending on the fieldbus used and the respective configuration, lower data rates and longer cycle times can be expected.	
Synchronization/clocks	
Distributed clocks	Yes
Time stamp format	64 bit in ns
Time resolution	1 ns (64 bit)
Time precision	25 ns within the station 100 ns via network (typ.) 1 µs via network (max.)
Synchronization functions	Synced operation Synced with oversampling operation
Synced output	AOV AOC DO / PWM
Synced output jitter	±175 ns
Latch input	AIV AIC RTD TC DI / CNT / INC
Field bus cycle time, min.	100 µs ¹⁾
1) Depending on the fieldbus used and the respective configuration, lower data rates and longer cycle times can be expected.	
Diagnostics	
Electronic type plate	Yes (application interface and in the engineering tool)
Machine readable type plate	Yes (QR code with type and part information and internet link)
Environmental conditions sensor	Integrated (temperature)
Operational indications	LED "MOD" (red/green) module status LED "CH" (red/green) channel status summary Numeric LED per channel (green) digital level of the channel
Error indications	Supply voltage too low Overload Wire break / open circuit Threshold value overshoot
Powerfail, logic supply	No
Powerfail, signal supply	Powerfail < 15.0 V (fallback > 17.5 V)
Overload/short-circuit	Yes, per output channel
Open circuit	Yes (analog I/O, digital I/O)

Diagnostics	
Mismatch output readback	Yes
Measurement range monitoring	Yes, upper/lower limit
Configurable threshold monitoring	Yes, configurable upper/lower limit
Energy supply	
Supply voltage, nominal	24 V DC
Supply voltage, range	18 V DC to 32 V DC
Power consumption from 24 V signal supply	3.7 W plus load supply
Maximum residual ripple 24 V signal supply	±2.4 V
Overcurrent protection required	No internal protection External protection with circuit breaker characteristic: B, C, D, Z or K Max. nominal current 8 A DC
Power dissipation, typ./max.	2.9 W / 4.0 W
Reverse polarity protection signal supply	Yes, continuously (up to -32 V)
Power consumption from backplane	1 W
Supply terminal block bridge	Yes (1+ on to 2+, 1- on to 2-)
Product safety	
Galvanic isolation	850 V AC
Galvanic isolation between supply groups	No
Galvanic isolation between inputs	No
Permitted potential difference between digital channels	No isolation between channels
Permitted potential difference between analog channels	No isolation between channels
Degree of protection acc. IEC 60529	IP40, terminal block IP30
Protection class acc. IEC 61010-1, IEC 61010-2-201	III
Overvoltage Category acc. IEC 61010-1	II
Rated impulse withstand voltage acc. IEC 61000-4-5	Supply DC 500 V DM 1000 V CM
Short-circuit protected, outputs	Yes, continuously
Keying of terminal block	Yes (6-fold per 4 contacts)
Environmental conditions	
Temperature, operating	Standard: -30 °C to +60 °C (standard mounting position) Extended Climate: -30 °C to +70 °C (standard mounting position)
Temperature, transport and storage	-40 °C to +85 °C
Installation altitude, max.	Up to 2000 m without temperature derating 2000 m to 4500 m: Reduction of the max. ambient temperature by 0.5 °C per 100 m elevation
Air pressure	106 kPa to 58 kPa (0 m to 4500 m)
Relative humidity, operation	Standard: 0 % to 100 % noncondensing Extended Climate: 0 % to 100 % with temporary condensation
Pollution degree acc. IEC 61010-1	Standard: 2, noncondensing Extended Climate: 2
Vibration	6 g (14.1 Hz to 500 Hz) 7.5 mm amplitude (2 Hz to 14.1 Hz) Test duration: 15 h
Shock	45 g max. (test scope 18 shocks) 20 g permanently (test scope 6000 shocks)

Approvals/certificates

Product safety	CE, UKCA cULus (NRAQ, NRAQ7)
Hazard area operation	ATEX in preparation
Maritime	DNV, LR, ABS, BV, RINA, KR, NK in preparation
Hazardous substances and waste treatment	RoHS, RoHS China, REACH, WEEE
IT/cybersecurity	ISO 27001 IEC 62443-4-1
Quality management	ISO 9001 for development and production

Engineering

Configuration tool	SolutionCenter (\geq V2.75)
Firmware package update	Yes (via SolutionCenter or console interface on the head module)

Mounting/installation

Mounting type	Inserting and screwing onto the backplane with integrated M4 screw
Ground connection for protection class I	No

Dimensions

Number of slots	1
Size unpacked W \times H \times D	95.7 mm \times 152.5 mm \times 23.3 mm
Mass unpacked	256 g

Order data

Part type designation	Part number	Description
UIO106	00028977-00	Universal analog/digital input/output module system M100 Configurable: 6x analog In \pm 0.01 V, 0.1 V, 1 V, 10 V, \pm 20 mA, 4 mA to 20 mA; TC, Pt100/Pt1000, 16 bit; analog Out \pm 10 V, 0 V to 10 V, 4 mA to 20 mA, 0 mA to 20 mA, 0 to 2 mA, 0 to 200 μ A, 14 bit; digital In 24 V sink/source, counter, encoder, 150 kHz; digital Out 24 V DC / 100 mA, 125 kHz, highside/lowside/pushpull, PWM / start-/hold-up pulsing; 0 to 6 additional channels depending on the signal type required, synchronization, time triggered output, time stamping, module-to-module communication transmitter and receiver, isolated from system, without terminal block
UIO106 EC	00038140-00	Like UIO106 with Extended Climate Range \ddagger

Accessories

Part type designation	Part number	Description
BPR1nn	00039235-nn	Backplane for DIN-rail mounting Active backplane system M100: BPR1nn with nn = 04 to 16 slots in increments of 1, as well as 20, 24, 28, 32 slots, for DIN-rail mounting; delivery without backplane slot covers and without mounting rail
BPR1nn EC	00039236-nn	Like BPR1nn with Extended Climate Range ☀️
BPS1nn	00039237-nn	Backplane for direct screw mounting Active backplane system M100: BPS1nn with nn = 04 to 16 slots in increments of 1, as well as 20, 24, 28, 32 slots, for direct screw mounting; delivery without backplane slot covers and without screws
BPS1nn EC	00039238-nn	Like BPS1nn with Extended Climate Range ☀️
TPI100_W24	00039178-00	Signal terminal block Completely removable terminal block, push-in spring connector for system M100, 24-way/contacts, pitch: 5.0 mm, female, conductors flexible 0.2 to 2.5 mm ² (24 to 13 AWG), solid 0.2 to 1.5 mm ² (24 to 16 AWG), with wire end ferrules 0.25 to 1.5 mm ² (23 to 16 AWG), stripping length: 10 mm, rating: 300 V / 8 A per contact, connector color: gray / push-release: yellow, labeling: 1 to 24
TPI100_W4	00039177-00	Supply terminal block Completely removable terminal block, push-in spring connector for system M100, 4-way/contacts, pitch: 5.0 mm, female, conductors flexible 0.2 to 2.5 mm ² (24 to 13 AWG), solid 0.2 to 1.5 mm ² (24 to 16 AWG), with wire end ferrules 0.25 to 1.5 mm ² (23 to 16 AWG), stripping length: 10 mm, rating: 300 V / 8 A per contact, connector color: gray / push-release: yellow, labeling: 1+/1-/2+/2-
TKP106	00038798-00	Keying element for signal terminal blocks and supply terminal blocks Keying element for signal terminal blocks and supply terminal blocks TPI100 for system M100, plastic ring with 6 keying elements